

# Handling, Transport & Storage general instructions

## KeyKeg safety warnings

**READ CAREFULLY BEFORE USE • KEG UNDER PRESSURE**

**HANDLE WITH CARE • PROFESSIONAL USE ONLY • DO NOT REUSE**


**STORAGE - KEEP BELOW 40°C**



Always deflate KeyKegs as soon as they are empty using either a red deflating tool or the KeyKeg coupler deflating valve. Do not deflate KeyKegs by any other method.



Dispense high CO<sub>2</sub> content beverages slowly.



Do not deflate KeyKegs in confined spaces if dispense gas is CO<sub>2</sub>.



Always keep KeyKegs stored below 40 °C.



Never reuse an empty KeyKeg.



Store KeyKegs in dark, shady places and avoid exposure to direct sunlight.



Never pierce or cut KeyKegs. Keep KeyKegs away from sharp objects.



Use a suitable coupler and tap, especially with higher acidity beverages like wine or cider.



Keep KeyKegs away from alkaline, caustic hydroxides or soapy cleaning products with a pH greater than 9.



Carry and store KeyKegs upright, never upside down. Do not roll KeyKegs along the floor.



Keep KeyKegs away from open fires or other heat sources.



Ensure tap coolers use the correct pressure for storage temperature and CO<sub>2</sub> content.

## PALLETIZING



10L



20L



30L

### EMPTY KEGS

Pallet size type

No. of layers

Kegs per layer

Kegs per pallet

Height

Orientation

Notes

Block / ISO2 (1.0 x 1.2 m - 39,37" x 47 3/4 ")		
7	4	4
20	20	12
140	80	48
2.43 m - 96"	2.42 m - 96"	2.42 m - 96"
Upside down		
Pallets are shrink wrapped with white foil and top is covered with a cardboard sheet.		

### FILLED KEGS

The maximum stacking height for filled KeyKegs is based on their mechanical properties and does not take local health and safety regulations or the maximum pallet, truck or container load into account.



10L



20L



30L

### FILLED KEGS

Max. no. of layers

Kegs per layer

Kegs per pallet

Height

Orientation

Max. stacking height in warehouse

Recommendations

5*	3*	3*
20	20	12
100	60	36
1.94 m - 76.4"	2.00 m - 78.7"	2.00 m - 78.7"
Right-side up		
10 layers	8 layers	8 layers
Pallets must be shrink wrapped and top covered with cardboard sheet. *With intermediate pallets.		

# Handling, Transport & Storage general instructions

## TRANSPORT OF EMPTY KEGS



### NUMBER OF PALLETS

	10L	20L	30L
45 ft. High Cube Pallet	26	26	26
40 ft. High Cube	22	22	22
40 ft. Reefer	20	20	20
Truck (13.6 mtr)	26	26	26
Truck with trailer (2 x 7m)	28	28	28
Jumbo truck (2 x 7.7 m)	28	28	28
US truck 48'	28	28	28
US truck 53'	30	30	30

## TRANSPORT OF EMPTY KEGS



### NUMBER OF EMPTY KEYKEGS

	10L	20L	30L
45 ft. High Cube Pallet	3640	2080	1248
40 ft. High Cube	3080	1760	1056
40 ft. Reefer	2800	1600	960
Truck (13.6 mtr)	3640	2080	1248
Truck with trailer (2 x 7m)	3920	2240	1344
Jumbo truck (2 x 7.7 m)	3920	2240	1344
US truck 48'	3940	2240	1344
US truck 53'	4200	2400	1440